

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

DO NOT MIX PRODUCT WITH OTHER MATERIAL UNLESS SPECIFIED BY MANUFACTURER.

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBONMONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IRRITATION OF THE RESPIRATORY TRACT; HEADACHE, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

WASH AFFECTED SKIN AREAS THOROUGHLY WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. INDUCE VOMITING AND CONTACT A PHYSICIAN OR YOUR NEAREST POISON CONTROL CENTER. NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON. TREAT SYMPTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP CARCINOGEN: NONE IARC MONOGRAPHS: OSHA REGULATED: NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE WHEN USED IN ACORDANCE WITH SAFE HANDLING AND USE INFORMATION.

EMERGENCY AND FIRST AID PROCEDURES

IF BREATHED: REMOVE TO FRESH AIR. IF IN EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF IN SKIN: REMOVE WITH SOAP AND WATER. REMOVE SOILED CLOTHING. INGESTION: INDUCE VOMITING PROMPTLY ACCORDING TO PHYSICIANS INSTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER VOMITING HAS BEEN INDUCED, GIVE TWO TEASPOONS OF BAKING SODA IN WATER.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER,BEFORE ATTEMPTING CLEAN UP,REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTION OF THIS MATERIAL SAFETY DATA SHEET. CONTAIN SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT MATERIAL. STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACORDANCE WITH LOCAL,STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 100F AND KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS

NONE

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS,SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREAS WITH UNRESTRICTED VENTILATION, AND DURING SANDING OR GRINDING OPERATION, USE NIOSH/NSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINATE CONCENTRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARD IN THE MIXING.

PROTECTIVE GLOVES

NOT REQUIRED

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYEWEAR WITH SPLASH GUARDS ARE RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING,SMOKING OR USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELEIVED BY THIS COMPANY TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR ITS ACCURACY. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE ONLY ONES WHICH EXIST. THE MANNER OF THAT USE AND WHEATHER THERE IS ANY INFRIGEMENT OF PATENTS IS THE SOLE RESPONSABILITY OF THE USER.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

DO NOT MIX PRODUCT WITH OTHER MATERIAL UNLESS SPECIFIED BY MANUFACTURER.

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBONMONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IRRITATION OF THE RESPIRATORY TRACT;HEADACHE,NAUSEA,DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IN CASE OF EYE CONTACT,FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

WASH AFFECTED SKIN AREAS THOROUGHLY WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. INDUCE VOMITING AND CONTACT A PHYSICIAN OR YOUR NEAREST POISON CONTROL CENTER. NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON. TREAT SYMPTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSSE DUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP CARCINOGEN: NONE IARC MONOGRAPHS: OSHA REGULATED: NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE WHEN USED IN ACORDANCE WITH SAFE HANDLING AND USE INFORMATION.

EMERGENCY AND FIRST AID PROCEDURES

IF BREATHED: ROMOVE TO FRESH AIR. IF IN EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF IN SKIN: REMOVE WITH SOAP AND WATER. REMOVE SOILED CLOTHING. INGESTION: INDUCE VOMITING PROMPTLY ACCORDING TO PHYSICIANS INSTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER VOMITING HAS BEEN INDUCED, GIVE TWO TEASPOONS OF BAKING SODA IN WATER.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER,BEFORE ATTEMPTING CLEAN UP,REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTION OF THIS MATERIAL SAFETY DATA SHEET. CONTAIN SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT MATERIAL. STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACORDANCE WITH LOCAL,STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 100F AND KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS

NONE

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS,SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREAS WITH UNRESTRICTED VENTILATION, AND DURING SANDING OR GRINDING OPERATION, USE NIOSH/NSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINATE CONCENTRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARD IN THE MIXING.

PROTECTIVE GLOVES

NOT REQUIRED

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYEWEAR WITH SPLASH GUARDS ARE RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING,SMOKING OR USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELEIVED BY THIS COMPANY TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR ITS ACCURACY. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE ONLY ONES WHICH EXIST. THE MANNER OF THAT USE AND WHEATHER THERE IS ANY INFRIGEMENT OF PATENTS IS THE SOLE RESPONSABILITY OF THE USER.

PRODUCT NAME: WALL COAT CERAMIC PAINT DEEP
PRODUCT CODE: WC-1402

HMIS CODES: H F R P
1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: LANCO & HARRIS CORP.
ADDRESS : 600 MID FLORIDA DRIVE
 ORLANDO, FL.
 32824

EMERGENCY PHONE : (407) 240-4000 DATE PRINTED : 8/26/2005
INFORMATION PHONE : (407) 240-4000 NAME OF PREPARER : DAVID MUNOZ

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE OSHA PEL: .5 mg/m3	26530-20-1	0.1	68 F
* 2-AMINO-2-METHYL-1-PROPANOL	174-68-5	1	180 F .13
* BENZYL CHLORIDE	100-44-7	NA	NA .02
* XYLENE TLV(ACGIH): 100 PPM STEL(ACGIH): 150 PPM PEO(OSHA): 100 PPM	1330-20-7	5.10	68 F .

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 279 F - 370 F SPECIFIC GRAVITY (H2O=1): 1.39
VAPOR DENSITY: LIGHTER THAN AIR. EVAPORATION RATE: UNKNOWN.
COATING V.O.C.: 51 gr/l MATERIAL V.O.C.: 89 gr/l
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: NORMAL

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: NON FLAMMABLE METHOD USED: NA
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 UPPER: 12.5

EXTINGUISHING MEDIA: CO2,WATER FOG,OTHER

SPECIAL FIREFIGHTING PROCEDURES

SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED,FOG NOZZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE DURING EMERGENCY CONDITIONS. OVEREXPOSURE CAN CAUSE DECOMPOSITION OF PRODUCT AND CREATE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

DO NOT MIX PRODUCT WITH OTHER MATERIAL UNLESS SPECIFIED BY MANUFACTURER.

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBONMONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IRRITATION OF THE RESPIRATORY TRACT; HEADACHE, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

WASH AFFECTED SKIN AREAS THOROUGHLY WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. INDUCE VOMITING AND CONTACT A PHYSICIAN OR YOUR NEAREST POISON CONTROL CENTER. NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON. TREAT SYMPTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP CARCINOGEN: NONE IARC MONOGRAPHS: OSHA REGULATED: NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE WHEN USED IN ACORDANCE WITH SAFE HANDLING AND USE INFORMATION.

EMERGENCY AND FIRST AID PROCEDURES

IF BREATHED: ROMOVE TO FRESH AIR. IF IN EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF IN SKIN: REMOVE WITH SOAP AND WATER. REMOVE SOILED CLOTHING. INGESTION: INDUCE VOMITING PROMPTLY ACCORDING TO PHYSICIANS INSTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER VOMITING HAS BEEN INDUCED, GIVE TWO TEASPOONS OF BAKING SODA IN WATER.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER,BEFORE ATTEMPTING CLEAN UP,REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTION OF THIS MATERIAL SAFETY DATA SHEET. CONTAIN SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT MATERIAL. STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACORDANCE WITH LOCAL,STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 100F AND KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS

NONE

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS,SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREAS WITH UNRESTRICTED VENTILATION, AND DURING SANDING OR GRINDING OPERATION, USE NIOSH/NSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINATE CONCENTRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARD IN THE MIXING.

PROTECTIVE GLOVES

NOT REQUIRED

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYEWEAR WITH SPLASH GUARDS ARE RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING,SMOKING OR USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELEIVED BY THIS COMPANY TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR ITS ACCURACY. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE ONLY ONES WHICH EXIST. THE MANNER OF THAT USE AND WHEATHER THERE IS ANY INFRIGEMENT OF PATENTS IS THE SOLE RESPONSABILITY OF THE USER.

PRODUCT NAME: WALL COAT CERAMIC PAINT ACCENT
PRODUCT CODE: WC-1403

HMIS CODES: H F R P
1 0 0

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: LANCO & HARRIS CORP.
ADDRESS : 600 MID FLORIDA DRIVE
 ORLANDO, FL.
 32824

EMERGENCY PHONE : (407) 240-4000 DATE PRINTED : 8/26/2005
INFORMATION PHONE : (407) 240-4000 NAME OF PREPARER : DAVID MUNOZ

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE OSHA PEL: .5 mg/m3	26530-20-1	0.1	68 F
* 2-AMINO-2-METHYL-1-PROPANOL	174-68-5	1	180 F .13
* BENZYL CHLORIDE	100-44-7	NA	NA .02
* XYLENE TLV(ACGIH): 100 PPM STEL(ACGIH): 150 PPM PEO(OSHA): 100 PPM	1330-20-7	5.10	68 F .

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 279 F - 370 F SPECIFIC GRAVITY (H2O=1): 1.36
VAPOR DENSITY: LIGHTER THAN AIR. EVAPORATION RATE: UNKNOWN.
COATING V.O.C.: 51 gr/l MATERIAL V.O.C.: 89 gr/l
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: NORMAL

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: NON FLAMMABLE METHOD USED: NA
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 UPPER: 12.5

EXTINGUISHING MEDIA: CO2,WATER FOG,OTHER

SPECIAL FIREFIGHTING PROCEDURES

SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED,FOG NOZZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE DURING EMERGENCY CONDITIONS. OVEREXPOSURE CAN CAUSE DECOMPOSITION OF PRODUCT AND CREATE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

DO NOT MIX PRODUCT WITH OTHER MATERIAL UNLESS SPECIFIED BY MANUFACTURER.

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBONMONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IRRITATION OF THE RESPIRATORY TRACT;HEADACHE,NAUSEA,DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IN CASE OF EYE CONTACT,FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

WASH AFFECTED SKIN AREAS THOROUGHLY WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. INDUCE VOMITING AND CONTACT A PHYSICIAN OR YOUR NEAREST POISON CONTROL CENTER. NEVER GIVE ANYTHING TO AN UNCONSSCIOUS PERSON. TREAT SYMPTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSSE DUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP CARCINOGEN: NONE IARC MONOGRAPHS: OSHA REGULATED: NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE WHEN USED IN ACORDANCE WITH SAFE HANDLING AND USE INFORMATION.

EMERGENCY AND FIRST AID PROCEDURES

IF BREATHED: ROMOVE TO FRESH AIR. IF IN EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF IN SKIN: REMOVE WITH SOAP AND WATER. REMOVE SOILED CLOTHING. INGESTION: INDUCE VOMITING PROMPTLY ACCORDING TO PHYSICIANS INSTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER VOMITING HAS BEEN INDUCED, GIVE TWO TEASPOONS OF BAKING SODA IN WATER.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER,BEFORE ATTEMPTING CLEAN UP,REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTION OF THIS MATERIAL SAFETY DATA SHEET. CONTAIN SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT MATERIAL. STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACORDANCE WITH LOCAL,STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 100F AND KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS

NONE

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS,SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREAS WITH UNRESTRICTED VENTILATION, AND DURING SANDING OR GRINDING OPERATION, USE NIOSH/NSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINATE CONCENTRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARD IN THE MIXING.

PROTECTIVE GLOVES

NOT REQUIRED

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYEWEAR WITH SPLASH GUARDS ARE RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING,SMOKING OR USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELEIVED BY THIS COMPANY TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR ITS ACCURACY. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE ONLY ONES WHICH EXIST. THE MANNER OF THAT USE AND WHEATHER THERE IS ANY INFRIGEMENT OF PATENTS IS THE SOLE RESPONSABILITY OF THE USER.